

# dannozzle®

## HAMMER ROTOR

5710138881383  
10071113



The Hammer Rotor is good for removal of concrete slag, rust, filler and other hard deposits in concrete, iron and cast iron pipes.

The Hammer Rotor consists of an eccentric rotor with 2x 85 degree M& ceramic nozzle inserts.

Has a stainless steel cape for protecting internal parts.

NOTICE: If used in other types of pipe besides the 3 described, the nozzle can cause severe damage to the pipe.

### HAMMERROTOR

| EAN Nr.       | Description | Weight (Kg) | Dimensions LxØ (mm) | Connection | Max. pressure | Max. Flow  | Nozzle inserts     | Scope of application |
|---------------|-------------|-------------|---------------------|------------|---------------|------------|--------------------|----------------------|
| 571013823059  | HR 111      | 1,1         | 111x62              | 3/8"       | 200 bar       | 75 l/min.  | BS 6xM6<br>RT 2xM6 | DN 100-300           |
| 5710138230600 | HR 107      | 1,1         | 107x62              | 1/2"       | 200 bar       | 138 l/min. | BS 6xM6<br>RT 2xM6 | DN 100-300           |

BS = Backwards Spray.

RT = Inserts on Rotor.

[www.dannozzle.dk](http://www.dannozzle.dk)

Østre Allé 6 • 9530 Støvring • tlf. +45 7020 7188 • fax +45 7020 7189 • sales@dannozzle.dk